

SodaBlast Systems

Complete System Package

SB-200-M-HEW

✓ Osha Safety Compliant



www.sbsllc.com

1800.216.7632

System Specifications and Components:

SodaBlaster Model SB-200 with Electric Remote Control

100 lb. / 2 cubic foot SodaBlast Pot
Venturi System
Two Hundred Ten CFM (cu.ft./min.) @ One Hundred Fifty PSI (lbs./sq.in.) PSI Manually set Depending on substrate to be Blasted
Twin High Capacity Evaporator Cooling System, Twelve Volt DC
¾" Inside Diameter Blast Hose
MT-3 Heavy Duty Air Receiver/Moisture Separator with Stainless De-Mister ASME Coded Vessel with two 2" inlet/outlet and a ¾" Drain
MT-125 Coalescing Filter Dryer
11½" ADC Body
Polycarbonate Bowl
Metal Bowl with Sight Glass
150~220 Pressure PSIG (MPa)
Air Coupling for Forced Air Feed Supply
In-Line Air Pressure Regulator
Round Pressure Gauge Square Embedded Type ¾" Body Type
Name Plate and Pressure Gauge in Imperial Units (PSI, °F)
Water Induction Nozzle (WIN) Double Venturi Blast Nozzle
5/16" Win #5 Tungsten Carbide Blast Nozzle
Abrasive Shut off Lever for Clean Air to Blow off Work Swivel Permits 360° Blast Hose Movement
Fifty Foot Section of Water Line
Fill Cap and Filling Funnel
Lifetime Factory Warranty

HEW Media Blast Pot

200 lb. / 2 cubic foot Abrasive Blasting Pot
Hardened Steel Elbow Insert
Kwik-Fit Hose Coupling
1" Inside Diameter Blast Hose
Swivel Permits 360° Blast Hose Movement
Abrasive Shut off Lever for Clean Air to Blow off Work
Air Coupling for Forced Air Feed Supply
Compressed Air Inlet Line
Air Inlet Nozzle – Special Hardened, Abrasion Resistant Steel
Special Filling Funnel

Eighty Horsepower John Deere Diesel Engine

26 Gallon Diesel Tank

Standard Instrumentation

Key Switch (On/Off)
Coolant Temperature Gauge
Oil Pressure Gauge
Safety Switch (Reset Button)
Battery Light

Sullivan Palatek Portable Air Compressor

Auxiliary Air Connections for Optional Tool Operations
Two ¾" Service Connections
Oil Level Sight Gauge
Large Full Length Lockable Tool Boxes on Each Side
Noise Level to Maximum of 76dBA at 7 meters
Automatic Shutdown and Protection System

Standard Instrumentation

Alternator Light
Fuel Level Gauge
Discharge Pressure Gauge
Hour Meter
Engine Oil Pressure Gauge
Engine Water Temperature Gauge

Industrial Grade All Steel deck Trailer with Electric Brakes

7 Pin Flat Connector
2" Trailer Ball
Ground to Level 14 ½" Center to the Ball
Needs Approximately 16" to Level the Trailer
Electric Brakes with Brake Away System
Diamond Plate Floor
Spare Tire Rack with Spare Tire
14' x 5' Work Deck
DOT Lighting

S-88 Air Fed Helmet

Bullard Model A1 Fresh Air Breathing Filter
Inner Lens
Vortex Heater/Air Conditioning Device
Jumper Hose for A1 Filter
Hose Sections for S-88 Helmet
See Breathe Carbon Monoxide Detector
No Calibration Required
No Maintenance, Replace Disposable Detector
No Remote Hook Up, No Wires or Tubing
• Total Tow Weight 4200 lbs., Tong Weight 415 lbs.
• Total Length 18' Width 7' Height 5.5'



SodaBlast Systems
5711 Schurmier Rd. Houston, TX 77048
(800) 216-7632 toll free (713) 868-8041 fax
www.sbsllc.com info@sbsllc.com